

What is claimed is new and desired to be protected
by Letters Patent is set forth in the appended claims:

1. A toothbrush assembly comprising:

a) an elongated handle including:

- i) a first end;
- ii) a second end;
- iii) a first and second side; and
- iv) a bristle head being positioned
on said first end and extending
from said first side.

and

b) a stand in the shape of first and second
feet, each of said first and second feet
being elongated to define a toe end and
together a common heel end, said first and
second feet being joined together and
positioned together to form a continuous
bottom supporting surface, said heel end of
each of said first and second feet being
positioned together to form a single heel
portion, said single heel portion including
a recess extending through a top side thereof
and towards a sole thereof for selectively
receiving said second end of said handle
therein, thereby retaining said handle in
a vertical position when said stand is
placed on a horizontal surface, said first
and second feet each including a side
surface, said side surfaces intersecting
one another in a common plain.

Sub
A1
Cont'd.

09505791, 021700
00/120, 16/50560

2. The toothbrush assembly as claimed in claim 1, further comprising a base connected to a bottom side of said stand.
3. The toothbrush assembly as claimed in claim 2, wherein said base includes a recess extending therethrough and in alignment with said recess in said stand for additionally receiving said second end of said handle therein.
4. The toothbrush assembly as claimed in claim 1, wherein said toe end of said first and second feet are at an acute angle to one another.
5. A toothbrush assembly comprising:
 - a) an elongated handle including:
 - i) a first end;
 - ii) a second end;
 - iii) a first and second side; and
 - iv) a bristle head being positioned on said first end and extending from said first side.
 - b) a stand in the shape of first and second feet and including a base on which said first and second feet are mounted, said first and second feet and said base each including a recess for receiving said second end of said handle therein, thereby retaining said handle in a vertical position when said stand and said base are placed on a horizontal surface.

and

add A27